An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : <u>info@ottokemi.com</u> Web : <u>www.ottokemi.com</u>

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Product identifiers

Product Name : Lithium sulphide, 99%+ Product Code: L 0522 CAS-No.: 12136-58-2

1.2. Relevant identified uses of the substance or mixture and uses advised against Use : Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet Company identification OTTO CHEMIE PVT LTD 101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Email info@ottokemi.com 1.4. Emergency telephone number Phone no.: + 91 22 2207 0099 (9:00am - 6:00 pm) **SECTION 2: Hazards identification** 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Acute toxicity, Oral (Category 3), H301 Skin corrosion (Sub-category 1B), H314 Serious eye damage (Category 1), H318 For the full text of the H-Statements mentioned in this Section, see Section 16. 2.2 Label elements Labelling according Regulation (EC) No 1272/2008 Pictogram Signal Word Danger Hazard statement(s) H301 Toxic if swallowed. H314 Causes severe skin burns and eye damage. Precautionary statement(s) P260 Do not breathe dusts or mists. Do not eat, drink or smoke when using this product. P270 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Supplemental Hazard information (EU) EUH029 Contact with water liberates toxic gas. 2.3 Other hazards This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. **SECTION 3: Composition/information on ingredients** 3.1 Substances

Formula : Li2S Molecular weight : 45,95 g/mol CAS-No. : 12136-58-2 EC-No. : 235-228-1 Component Classification Concentration

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : info@ottokemi.com Web : www.ottokemi.com

Lithium sulfide			
CAS-No. 12136-58-2	Acute Tox. 3; Skin Corr.	<= 100 %	
EC-No. 235-228-1	1B; Eye Dam. 1; H301,		
	H314, H318		
Earth - fall to the fill of the sentence of the set in this October 10			

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor

in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with

water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Unsuitable extinguishing media Water Foam 5.2 Special hazards arising from the substance or mixture Sulfur oxides Lithium oxides Not combustible. May not get in touch with: Water Ambient fire may liberate hazardous vapours. 5.3 Advice for firefighters Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing. 5.4 Further information Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact.
Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.
For personal protection see section 8.
6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : <u>info@ottokemi.com</u> Web : <u>www.ottokemi.com</u>

(see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area. Avoid generation of dusts. 6.4 Reference to other sections For disposal see section 13. **SECTION 7: Handling and storage** 7.1 Precautions for safe handling Advice on safe handling Keep workplace dry. Do not allow product to come into contact with water. Hygiene measures Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2. 7.2 Conditions for safe storage, including any incompatibilities Storage conditions Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons. Never allow product to get in contact with water during storage. Storage stability Recommended storage temperature 2 - 8 °C Store under inert gas. Stench. hygroscopic Storage class Storage class (TRGS 510): 6.1B: Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials 7.3 Specific end use(s) Apart from the uses mentioned in section 1.2 no other specific uses are stipulated SECTION 8: Exposure controls/personal protection 8.1 Control parameters Ingredients with workplace control parameters 8.2 Exposure controls Personal protective equipment Eye/face protection Use equipment for eve protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles Body Protection protective clothing Respiratory protection required when dusts are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system. Recommended Filter type: Filter type P3 The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented. Control of environmental exposure Do not let product enter drains. **SECTION 9: Physical and chemical properties** 9.1 Information on basic physical and chemical properties a) Physical state powder b) Color beige c) Odor Stench Melting point/range: 900 - 975 °C d) Melting

point/freezing point e) Initial boiling point and boiling range f) Flammability (solid,gas) The product is not flammable.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : info@ottokemi.com Web : www.ottokemi.com

g) Upper/lower flammability or explosive limits h) Flash point i) Autoignition temperature j) Decomposition temperature k) pH l) Viscosity

m) Water solubility n) Partition coefficient: n-octanol/water o) Vapor pressure p) Density Relative density q) Relative vapour density r) Particle characteristics s) Explosive properties t) Oxidizing properties 9.2 Other safety information No data available

SECTION 10: Stability and reactivity

10.1 Reactivity
No data available
10.2 Chemical stability
sensitive to moisture
10.3 Possibility of hazardous reactions
No data available
10.4 Conditions to avoid
Contact with acids liberates very toxic gas. Avoid moisture.
no information available
10.5 Incompatible materials
Do not store near acids.
10.6 Hazardous decomposition products
In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals: Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg Inhalation LC50 Rat: > 50mg/L. Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH. Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant). Special Remarks on Toxicity to Animals: Not available. Special Remarks on other Toxic Effects on Humans: Not available. Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity
No data available
12.2 Persistence and degradability
The methods for determining biodegradability are not applicable to inorganic substances.
12.3 Bioaccumulative potential
No data available
12.4 Mobility in soil

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

No data available

Not applicable No data available

No data available

No data available Viscosity, kinematic: No data available Viscosity, dynamic: No data available No data available Not applicable for inorganic substances

No data available 1,66 g/mL at 25 °C - lit. No data available No data available

No data available

No data available none

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : info@ottokemi.com Web : www.ottokemi.com

No data available 12.5 Results of PBT and vPvB assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. 12.6 Endocrine disrupting properties Product: Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. 12.7 Other adverse effects No data available **SECTION 13: Disposal considerations** 13.1 Waste treatment methods No data available **SECTION 14: Transport information** 14.1 UN number ADR/RID: 2923 IMDG: 2923 IATA: 2923 14.2 UN proper shipping name ADR/RID: CORROSIVE SOLID, TOXIC, N.O.S. (Lithium sulfide) CORROSIVE SOLID, TOXIC, N.O.S. (Lithium sulfide) IMDG: IATA: Corrosive solid, toxic, n.o.s. (Lithium sulfide) 14.3 Transport hazard class(es) ADR/RID: 8 (6.1) IMDG: 8 (6.1) IATA: 8 (6.1) 14.4 Packaging group ADR/RID: II IMDG: II IATA: II 14.5 Environmental hazards ADR/RID: no IMDG Marine pollutant: no IATA: no 14.6 Special precautions for user Tunnel restriction code : (E) Further information : No data available **SECTION 15: Regulatory information** 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. National legislation Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : ACUTE TOXIC : OTHER HAZARDS Other regulations Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work. 15.2 Chemical Safety Assessment For this product a chemical safety assessment was not carried out

Section 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his

DISCLAIMER


Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

Otto Chemie Pvt Ltd - provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841 Email : info@ottokemi.com Web : www.ottokemi.com

activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.



DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.