

An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Product identifiers

Product Name: Lithium fluoride, 99.995%

Product Code: L 4304 CAS-No.: 7789-24-4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use: Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification OTTO CHEMIE PVT LTD

101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate,

Chinchpada, Vasai East, Waliv, Maharashtra 401208.

Email info@ottokemi.com

1.4. Emergency telephone number

Phone no.: + 91 22 2207 0099 (9:00am - 6:00 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Acute toxicity, (Category 3) H301: Toxic if swallowed.

Skin irritation, (Category 2) H315: Causes skin irritation.

Eye irritation, (Category 2) H319: Causes serious eye irritation.

Specific target organ toxicity - H335: May cause respiratory irritation.

single exposure, (Category 3),

Respiratory system 2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word Danger

Hazard Statements

H301 Toxic if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

H335
Precautionary Statements

P261 Avoid breathing dust.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

May cause respiratory irritation.

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard information (EU)

EUH032 Contact with acids liberates very toxic gas.

Reduced Labeling (<= 125 ml)

Pictogram

H301

Signal Word Danger

Hazard Statements

Toxic if swallowed.

Precautionary Statements

P264 Wash skin thoroughly after handling.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

Supplemental Hazard information (EU)

EUH032 Contact with acids liberates very toxic gas.

2.3 Other hazards

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001: 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Weak hydrogen fluoride-releaser

SECTION 3: Composition/information on ingredients

3.1 Substances Formula: FLi

Molecular weight: 25,94 g/mol

CAS-No.: 7789-24-4 FC-No : 232-152-0

20 110: : 202 102 0		
Component	Classification	Concentration
Lithium fluoride		
CAS-No. 7789-24-4	Acute Tox. 3; Skin Irrit. 2;	<= 100 %
EC-No. 232-152-0	Eye Irrit. 2; STOT SE 3;	
	H301, H315, H319, H335	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures General advice

Hydrofluoric (HF) acid burns require immediate and specialized first aid and medical treatment. Symptoms may be delayed up to 24 hours depending on the concentration of HF. After decontamination with water, further damage can occur due to penetration/absorption of the fluoride ion. Treatment should be directed toward binding the fluoride ion as well as the effects of exposure. Skin exposures can be treated with a 2.5% calcium gluconate gel repeated until burning ceases. More serious skin exposures may require subcutaneous calcium gluconate except for digital areas unless the physician is experienced in this technique, due to the potential for tissue injury from increased pressure. Absorption can readily occur through the subungual areas and should be considered when undergoing decontamination. Prevention of absorption of the fluoride ion in cases of ingestion can be obtained by giving milk, chewable calcium carbonate tablets or Milk of Magnesia to conscious victims. Conditions such as hypocalcemia, hypomagnesemia and cardiac arrhythmias should be monitored for, since they can occur after exposure. Show this material safety data sheet to the doctor in attendance. If inhaled

After inhalation: fresh air.

In case of skin contact

First treatment with calcium gluconate paste. In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as guickly as possible.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001 : 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Hydrogen fluoride

Lithium oxides

Combustible.

Mixture with combustible ingredients.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by

keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area.

Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Do not store near acids.

Storage class

Storage class (TRGS 510): 6.1D: Non-combustible, acute toxic Cat.3 / toxic hazardous materials or hazardous materials causing chronic effects

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

OTTO CHEMIE PVT LTD

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min Material tested:KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de). Splash contact Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested:KCL 741 Dermatril® L

Body Protection protective clothing Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to

the used respiratory protection system.

Recommended Filter type: Filter type P3

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state powder b) Color No data available

c) Odor
No data available
d) Melting point/rang

d) Melting point/range: 845 °C point/freezing point

e) Initial boiling point

No data available

and boiling range
f) Flammability (solid,gas)

The product is not flammable.

g) Upper/lower flammability or explosive limits

h) Flash point Not applicable
i) Autoignition No data available

temperature j) Decomposition No data available

temperature
k) pH 7,0 - 8,5 at 0,26 g/l at 25 °C
l) Viscosity Viscosity, kinematic: No data available
Viscosity, dynamic: No data available

m) Water solubility ca.0,3 g/l at 20 °C n) Partition coefficient: No data available n-octanol/water

o) Vapor pressure No data available p) Density 2,64 g/mL at 25 °C Relative density No data available q) Relative vapour No data available

density
r) Particle
No data available

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

OTTO CHEMIE PVT LTD

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

characteristics

s) Explosive properties

t) Oxidizing properties

9.2 Other safety information

No data available

No data available No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally

be assumed

Contact with acids liberates very toxic gas.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

Violent reactions possible with:

halogen-halogen compounds

Generates dangerous gases or fumes in contact with:

acids

Generates dangerous gases or fumes in contact with:

Acids

10.4 Conditions to avoid

Avoid moisture.

no information available

10.5 Incompatible materials

glass

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity

to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to daphnia

and other aquatic

invertebrates

EC50 - Daphnia - 152,37 mg/l - 48 h

Remarks: (calculated)

Toxicity to algae static test NOEC - Desmodesmus subspicatus (green algae) - 25 mg/l

- 72 h

(OECD Test Guideline 201)

Remarks: The value is given in analogy to the following substances:

Lithium chloride

static test ErC50 - Desmodesmus subspicatus (green algae) - > 400

mg/l - 72 h

(OECD Test Guideline 201)

Remarks: The value is given in analogy to the following substances:

Lithium chloride

Toxicity to daphnia

and other aquatic

invertebrates(Chronic

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

OTTO CHEMIE PVT LTD

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

toxicity)

NOEC - Daphnia - 14,1 mg/l - 21 d 12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment: The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number ADR/RID: 3288 IMDG: 3288

14.2 UN proper shipping name

ADR/RID: TOXIC SOLID, INORGANIC, N.O.S. (Lithium fluoride) IMDG: TOXIC SOLID, INORGANIC, N.O.S. (Lithium fluoride)

IATA: Toxic solid, inorganic, n.o.s. (Lithium fluoride)

14.3 Transport hazard class(es)

ADR/RID: 6.1 14.4 Packaging group

IATA: 3288

IATA: no

ADR/RID: III IATA: III

14.5 Environmental hazards

IMDG Marine pollutant: no

ADR/RID: no 14.6 Special precautions for user Tunnel restriction code : (E)

Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No.

1907/2006.

National legislation

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards

involving dangerous substances.

H2 ACUTE TOXIC

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Section 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

