## otto chemie pvt ltd

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

### **MATERIAL SAFETY DATA SHEET (MSDS)**

#### **SECTION 1. Product identifiers**

Product name: 2-Mercapto ethanol, for molecular biology, 99%

Product Code: M 1628 CAS No: 60-24-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use: Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification OTTO CHEMIE PVT LTD

101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate,

Chinchpada, Vasai East, Waliv, Maharashtra 401208.

Email info@ottokemi.com

1.4. Emergency telephone number

Phone no.: + 91 22 2207 0099 (9:00am - 6:00 pm).

#### **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Acute toxicity, (Category 3) Acute toxicity, (Category 3)

Acute toxicity, (Category 2)

Skin irritation, (Category 2) Serious eye damage, (Category

Skin sensitization, (Sub-category

1A)

Reproductive toxicity, (Category

Specific target organ toxicity repeated exposure, (Category 2),

Liver. Heart

Short-term (acute) aquatic

hazard, (Category 1)

Long-term (chronic) aquatic

hazard, (Category 2)

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram Signal Word

Hazard Statements

H301 + H331

H310

H315

H317

H318

H361f

H373

H410

**Precautionary Statements** 

P273

P280

P301 + P310

P302 + P352 + P310

H301: Toxic if swallowed.

H331: Toxic if inhaled.

H310: Fatal in contact with skin. H315: Causes skin irritation.

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

H361f: Suspected of damaging fertility.

H373: May cause damage to organs through prolonged or repeated exposure if

swallowed.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting

effects.

#### Danger

Toxic if swallowed or if inhaled.

Fatal in contact with skin.

Causes skin irritation

May cause an allergic skin reaction.

Causes serious eye damage. Suspected of damaging fertility.

May cause damage to organs (Liver, Heart) through prolonged

or repeated exposure if swallowed.

Very toxic to aquatic life with long lasting effects.

Avoid release to the environment.

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. IF ON SKIN: Wash with plenty of water. Immediately call a

POISON CENTER/ doctor.

#### DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

## otto chemie pvt ltd

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor. P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Supplemental Hazard

Statements

Reduced Labeling (<= 125 ml)

Pictogram

Signal Word

Hazard Statements

H310

H317 H318 H361f H301 + H331

**Precautionary Statements** 

P280

P301 + P310

P302 + P352 + P310

P304 + P340 + P311

P305 + P351 + P338

Danger

none

Fatal in contact with skin.

May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging fertility.

Toxic if swallowed or if inhaled.

Wear protective gloves/ protective clothing/ eye protection/ face

IF SWALLOWED: Immediately call a POISON CENTER/ doctor. IF ON SKIN: Wash with plenty of water. Immediately call a

POISON CENTER/ doctor.

IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Call a POISON CENTER/ doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. none

Supplemental Hazard

Statements

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent. bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**Ecological information:** 

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Stench.

Stench., Rapidly absorbed through skin.

## **SECTION 3: Composition/information on ingredients**

3.1 Substances

Synonyms 2-Hydroxyethylmercaptan

β-Mercaptoethanol beta mercaptoethanol Thioethylene glycol

**BME** 

: C2H6OS Formula Molecular weight : 78,13 g/mol CAS-No. : 60-24-2 EC-No. : 200-464-6

Component	Classification	Concentration
Mercaptoethanol		
CAS-No. 60-24-2	Acute Tox. 3; Acute Tox. 2; Skin Irrit. 2	; <= 100 %
EC-No. 200-464-6	Eye Dam. 1; Skin Sens. 1A; Repr. 2;	
	STOT RE 2; Aquatic Acute 1; Aquatic	

#### DISCI AIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Chronic 2; H301, H331, H310, H315, H318, H317, H361f, H373, H400, H411 M-Factor - Aquatic Acute: 1	
--	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4: First aid measures**

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Sulfur oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

#### DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g.

Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections For disposal see section 13.

## **SECTION 7: Handling and storage**

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage stabilityRecommended storage temperature

2 - 8 °C

Storage class

Storage class (TRGS 510): 6.1A: Combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

### SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Worker DNEL, acute	inhalation	Systemic effects	0,17 mg/m3
Worker DNEL, longterm	inhalation	Health effect	0,17 mg/m3
Worker DNEL, longterm	dermal	Health effect	
Worker DNEL, acute	dermal	Health effect	

## Predicted No Effect Concentration (PNEC)

Compartment	Value
Fresh water	0,0004 mg/l
Sea water	0,00004 mg/l
Aquatic intermittent release	0,004 mg/l
Sewage treatment plant	60 mg/l
Fresh water sediment	0,0015 mg/kg
Sea sediment	0,00015 mg/kg
Soil	0.000063 mg/kg

### 8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other

#### DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum laver thickness: 0.7 mm Break through time: 480 min

Material tested:Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de). Splash contact Material: Nitrile rubber

Minimum layer thickness: 0,4 mm Break through time: 120 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

**Body Protection** protective clothing Respiratory protection

Recommended Filter type: Filter B-(P3)

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure Do not let product enter drains.

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

a) Physical state

b) Color c) Odor

d) Melting

point/freezing point

e) Initial boiling point and boiling range

f) Flammability (solid,

gas)

g) Úpper/lower flammability or

explosive limits

h) Flash point i) Autoignition

temperature j) Decomposition

temperature k) pH

I) Viscosity

m) Water solubility n) Partition coefficient:

n-octanol/water o) Vapor pressure p) Density

Relative density q) Relative vapor density

r) Particle characteristics

s) Explosive properties

liquid colorless characteristic

Melting point: < -50 °C

157 °C

No data available

Upper explosion limit: 18 %(V) Lower explosion limit: 2,3 %(V)

74 °C - closed cup No data available

No data available

4,5 - 6 at 500 g/l at 20 °C

Viscosity, kinematic: No data available Viscosity, dynamic: 3,4 mPa.s at 20 °C

at 20 °C soluble

log Pow: -0,056 at 25 °C - Bioaccumulation is not expected.

0,76 hPa at 20 °C 1,114 g/mL at 25 °C No data available No data available

No data available

Not classified as explosive.

#### DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

none

t) Oxidizing properties 9.2 Other safety information Relative vapor density

2,70 - (Air = 1.0)

### **SECTION 10: Stability and reactivity**

10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

Violent reactions possible with:

Strong oxidizing agents

A risk of explosion and/or of toxic gas formation exists with the following substances:

Acids

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Metals, Oxidizing agents, Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

### **SECTION 11: Toxicological information**

11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity

to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

### **SECTION 12: Ecological information**

12.1 Toxicity

Toxicity to fish static test LC50 - Leuciscus idus (Golden orfe) - 37 mg/l - 96 h

(DIN 38412 T15)

Toxicity to daphnia

and other aquatic

invertebrates

static test EC50 - Daphnia magna (Water flea) - 0,4 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Desmodesmus subspicatus (green algae) - 19

mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - Pseudomonas putida - 125 mg/l - 17 h

(DIN 38 412 Part 8)

Toxicity to daphnia

and other aquatic

invertebrates (Chronic

toxicity)

semi-static test NOEC - Daphnia magna (Water flea) - > 0,0632 mg/l

- 21 d

(OECD Test Guideline 211)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 60 d

Result: 69 % - Not readily biodegradable.

(OECD Test Guideline 310)

Remarks: (ECHA)

#### DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

IMDG: 2966

IMDG: 6.1

IMDG: II

IMDG Marine pollutant: yes

IATA: 2966

IATA: 6.1

IATA: II

IATA: no

Biochemical Oxygen 105 mg/g

Demand (BOD) Remarks: (IUCLID)

Chemical Oxygen

Demand (COD)

1,894 mg/g

Remarks: (IUCLID)

12.3 Bioaccumulative potential

Does not accumulate in organisms.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission

Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

### **SECTION 13: Disposal considerations**

13.1 Waste treatment methods

No data available

#### **SECTION 14: Transport information**

14.1 UN number ADR/RID: 2966

14.2 UN proper shipping name

ADR/RID : THIOGLYCOL

IMDG : THIOGLYCOL

IATA : Thioglycol 14.3 Transport hazard class(es)

ADR/RID: 6.1

14.4 Packaging group

ADR/RID: II

14.5 Environmental hazards

ADR/RID: yes

14.6 Special precautions for user

Tunnel restriction code : (D/E)

Further information : No data available

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the

substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No.

1907/2006.

National legislation

Seveso III: Directive 2012/18/EU of the

European Parliament and of the Council

on the control of major-accident hazards

involving dangerous substances.

H2 ACUTE TOXIC

E1 ENVIRONMENTAL HAZARDS

**H2 ACUTE TOXIC** 

E1 ENVIRONMENTAL HAZARDS

Other regulations

#### DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance

#### **SECTION 16: Other Information**

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

