

OTTO CHEMIE PVT LTD

201, 51-53 Maroo Bhavan, Kalbadevi, Mumbai – 400002, India. Tel : + 91 22 2207 0099 / 6638 2599

Email : info@ottokemi.com, Web : www.ottokemi.com

ISO 9001: 2015

MATERIAL SAFETY DATA SHEET

SECTION 1 Product identifiers

Product name : Sodium hydroxide 2 mol/L (2N) solution

Product Code: S 3007

CAS-No. : 1310-73-2

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Corrosive to Metals (Category 1), H290

Skin corrosion (Sub-category 1A), H314

Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal Word

Danger

Hazard statement(s)

H290

May be corrosive to metals.

H314

Causes severe skin burns and eye damage.

Precautionary statement(s)

P234

Keep only in original packaging.

P260

Do not breathe dust.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard

none

Statements

Reduced Labeling

(<= 125 ml)

Pictogram

Signal Word

Danger

Hazard statement(s)

H314

Causes severe skin burns and eye damage.

Precautionary statement(s)

P260

Do not breathe dust.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard

none

Statements

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : 'Caustic soda'

Formula : HNaO

Molecular weight : 40,00 g/mol

CAS-No. : 1310-73-2

EC-No. : 215-185-5

Component	Classification	Concentration
sodium hydroxide		
CAS-No. 1310-73-2 EC-No. 215-185-5	Met. Corr. 1; Skin Corr. 1A; Eye Dam. 1; H290, H314, H318 Concentration limits: >= 5 %: Skin Corr. 1A, H314; 2 - < 5 %: Skin Corr. 1B, H314; 0,5 - < 2 %: Skin Irrit. 2, H315; 0,5 - < 2 %: Eye Irrit. 2, H319; >= 0,4 %: Met. Corr. 1, H290;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist.

Remove contact lenses.

If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Sodium oxides

Sodium oxides

Not combustible.

Ambient fire may liberate hazardous vapours.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact.

Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

No metal containers.

Tightly closed. Dry.

Storage class

Storage class (TRGS 510): 8B: Non-combustible, corrosive hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Long-term local effects	1 mg/m ³
Consumers	Inhalation	Long-term local effects	1 mg/m ³

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm

Break through time: 480 min

Material tested:KCL 741 Dermatril® L

Body Protection

protective clothing

Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type P2

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state	pellets
b) Color	white
c) Odor	odorless
d) Melting point/freezing point	Melting point/range: 318 °C - lit.
e) Initial boiling point and boiling range	1.390 °C at 1.013 hPa
f) Flammability (solid, gas)	The product is not flammable.
g) Upper/lower flammability or explosive limits	No data available
h) Flash point	Not applicable
i) Autoignition temperature	No data available
j) Decomposition temperature	No data available
k) pH	ca. > 14 at 100 g/l at 20 °C
l) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
m) Water solubility	1.090 g/l at 20 °C
n) Partition coefficient: n-octanol/water	Not applicable for inorganic substances
o) Vapor pressure	No data available
p) Density	2,13 g/cm ³ at 20 °C
Relative density	No data available
q) Relative vapor density	No data available
r) Particle characteristics	No data available
s) Explosive properties	No data available
t) Oxidizing properties none	
9.2 Other safety information	
Relative vapor density	1,38 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with:

Acetone
Chlorine
Ethylene oxide
Fluorine
Hydrogen halides
Hydrazine hydrate
hydroxylamine
Acid anhydrides
Acrolein
Acid chlorides
Acids
sulfuric acid
Chloroform
Water
hydrogen peroxide
anhydrides
phosphides
halogen-halogen compounds
trichloroethene

can decompose violently in contact with:

Organic Substances
hydrogen sulphide
Risk of ignition or formation of inflammable gases or vapours with:
powdered aluminium
Ammonium salts

persulfates
Sodium borohydride
phosphorus
Oxides of phosphorus
Halogenated hydrocarbon
Light metals
Metals
Risk of explosion/exothermic reaction with:
Bromine
Calcium
in powder form
furfuryl alcohol
Nitromethane
Peroxides
organic nitro compounds
Nitriles
Acrylic monomers
Chloroform
with
Acetone
Nitrobenzene
with
Methanol
Nitrobenzene
with
salts
magnesium
Zinc
and
Tin

(in the presence of atmospheric oxygen and/or moisture)

10.4 Conditions to avoid

no information available

10.5 Incompatible materials

Aluminum, brass, Metals, metal alloys, Zinc, Tin

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity

to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish LC50 - *Gambusia affinis* (Mosquito fish) - 125 mg/l - 96 h

Remarks: (ECOTOX Database)

Toxicity to daphnia

and other aquatic

invertebrates

EC50 - *Ceriodaphnia* (water flea) - 40,4 mg/l - 48 h

Remarks: (ECHA)

Toxicity to bacteria EC50 - *Photobacterium phosphoreum* - 22 mg/l - 15 min

Remarks: (External MSDS)

12.2 Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent,

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

Neutralisation possible in waste water treatment plants.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1823

IMDG: 1823

IATA: 1823

14.2 UN proper shipping name

ADR/RID: SODIUM HYDROXIDE, SOLID

IMDG: SODIUM HYDROXIDE, SOLID

IATA: Sodium hydroxide, solid

14.3 Transport hazard class(es)

ADR/RID: 8

IMDG: 8

IATA: 8

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Other regulations

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

Section 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.