An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate,

Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Creation Date: 11-05-2025 Revision Date: 17-10-2030

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1. Product identifiers

Product name: Tetra ethoxy silane, 98%

Product Code: T 1376 CAS No: 78-10-4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use: Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification OTTO CHEMIE PVT LTD

101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate,

Chinchpada, Vasai East, Waliv, Maharashtra 401208.

Email info@ottokemi.com

1.4. Emergency telephone number

Phone no.: + 91 22 2207 0099 (9:00am - 6:00 pm).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flammable liquids, (Category 3) Acute toxicity, (Category 4)

Eye irritation, (Category 2) Specific target organ toxicity -

single exposure, (Category 3),

Respiratory system 2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram Signal Word

Hazard Statements

H226 H319

H332 H335

Precautionary Statements

P210

P233 P240 P241

P304 + P340 + P312

P305 + P351 + P338

Supplemental Hazard

Statements

Reduced Labeling (<= 125 ml)

Pictogram

Signal Word Hazard Statements Precautionary Statements H226: Flammable liquid and vapor.

H332: Harmful if inhaled.

H319: Causes serious eye irritation. H335: May cause respiratory irritation.

Warning

Flammable liquid and vapor. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking. Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue

rinsing. none

.....

Warning none none

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Supplemental Hazard

none

Statements

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms: Tetraethoxysilane

Orthosilicic acid tetraethyl ester

Formula : C8H20O4Si Molecular weight : 208,33 g/mol CAS-No. : 78-10-4 EC-No. : 201-083-8

| Component | Classification | Concentration |
|---------------------|---|---------------|
| tetraethyl silicate | | |
| CAS-No. 78-10-4 | Flam. Liq. 3; Acute Tox. 4; Eye Irrit. 2; | <= 100 % |
| EC-No. 201-083-8 | STOT SE 3; H226, H332, H319, H335 | |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with

water/ shower.

n case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact

lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

silicon oxides

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Under fire conditions, material may decompose to form flammable and/or explosive mixtures in air.Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®).

Dispose of properly. Clean up affected area. 6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Store under nitrogen.

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and

sources of ignition.

Moisture sensitive.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Predicted No Effect Concentration (PNEC)

| Compartment | Value |
|------------------------|-------------|
| Fresh water | 0,192 mg/l |
| Sea water | 0,0192 mg/l |
| Fresh water sediment | 0,83 mg/kg |
| Sea sediment | 0,083 mg/kg |
| Soil | 0,05 mg/kg |
| Sewage treatment plant | 4000 mg/l |

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Aquatic intermittent release

10 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,4 mm Break through time: 480 min

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please Splash contact

Material: Chloroprene

Minimum layer thickness: 0,65 mm Break through time: 240 min Material tested:KCL 720 Camapren®

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type ABEK

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state

b) Color

c) Odor

d) Melting

point/freezing point

e) Initial boiling point

and boiling range

f) Flammability (solid,

gas)

g) Úpper/lower flammability or explosive limits

h) Flash point i) Autoignition

temperature

j) Decomposition temperature

k) pH I) Viscosity

m) Water solubility

liquid colorless

No data available

Melting point: -82,5 °C at ca.1.013 hPa

168 °C - lit.

No data available

Upper explosion limit: 23 %(V) Lower explosion limit: 1,3 %(V)

45 °C - closed cup - DIN 51755 Part 1

222 °C at 960,8 hPa No data available

No data available

Viscosity, kinematic: No data available Viscosity, dynamic: 0,6 mPa.s at 20 °C 1,49 g/l at 23 °C at 7 hPa - soluble

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

n) Partition coefficient:

n-octanol/water

o) Vapor pressure

p) Density

Relative density

q) Relative vapor

density

r) Particle

ćharacteristics

s) Explosive properties

t) Oxidizing properties

9.2 Other safety information

Relative vapor

density

log Pow: 3,18 at 40 °C - Bioaccumulation is not expected.

< 1 hPa at 20 °C

0,933 g/cm3 at 20 °C - lit.

No data available

No data available

No data available

Not classified as explosive.

none

7,19 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

May decompose on exposure to moist air or water.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

rubber, various plastics

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity

to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish semi-static test LC50 - Danio rerio (zebra fish) - > 245 mg/l - 96 h

(Regulation (EC) No. 440/2008, Annex, C.1)

Toxicity to daphnia

and other aquatic

invertebrates

flow-through test EC50 - Daphnia magna (Water flea) - > 75 mg/l -

48 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata - > 100 mg/l - 72

h

(OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - activated sludge - > 100 mg/l - 3 h

(OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 98 % - Readily biodegradable.

(Directive 67/548/EEC Annex V, C.4.A.)

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

IMDG: 1292

IMDG: 3

IMDG: III

IMDG Marine pollutant: yes

IATA: 1292

IATA: 3

IATA: III

IATA: no

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number ADR/RID: 1292

14.2 UN proper shipping name

ADR/RID : TETRAETHYL SILICATE

IMDG : TETRAETHYL SILICATE

IATA : Tetraethyl silicate

14.3 Transport hazard class(es)

ADR/RID: 3

14.4 Packaging group

ADR/RID: III

14.5 Environmental hazards

ADR/RID: yes 14.6 Special precautions for user

Tunnel restriction code : (D/E)

Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the

substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No.

1907/2006.

Authorisations and/or restrictions on use

National legislation

Seveso III: Directive 2012/18/EU of the

European Parliament and of the Council

on the control of major-accident hazards

involving dangerous substances.

P5c FLÄMMÄBLE LIQUIDS

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or

stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

SECTION 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Creation Date: 11-05-2025 Revision Date: 17-10-2030

