101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: +91 9820041841

Email: info@ottokemi.com, Web: www.ottokemi.com

MATERIAL SAFETY DATA SHEET

1 Identification

1.1GHS Product identifier 2-Butoxyethanol, puriss GR 99%+

Code: B 2277

2. Hazard identification

2.1 Classification of the substance or mixture

Acute toxicity - Oral, Category 4 Acute toxicity - Dermal, Category 4 Skin irritation, Category 2

Eye irritation, Category 2 Acute toxicity - Inhalation, Category 4

2.2GHS label elements, including precautionary statements

Pictogram(s)

Signal word

Hazard statement(s)

Precautionary statement(s)

Prevention

Response

Storage Disposal

3. Composition/information on ingredients

3.1Substances

Chemical name Common names and synonyms CAS number EC number Concentration 2-butoxyethanol 2-butoxyethanol 111-76-2 100% none

4.First-aid measures

4.1 Description of necessary first-aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

Fresh air, rest. Refer for medical attention.

In case of skin contact

Remove contaminated clothes. Rinse skin with plenty of water or shower. Refer for medical attention .

In case of eve contact

First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.

www.ottokemi.com

Warning

H312 Harmful in contact with skin H315 Causes skin irritation H319 Causes serious eye irritation H332 Harmful if inhaled

H302 Harmful if swallowed

P264 Wash ... thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor/\u2026if you feel unwell.

P330 Rinse mouth.

P302+P352 IF ON SKIN: Wash with plenty of water/...
P312 Call a POISON CENTER/doctor/u2026if you feel unwell.

P321 Specific treatment (see ... on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

none

P501 Dispose of contents/container to ...

2.3Other hazards which do not result in classification

101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: +91 9820041841

Email: info@ottokemi.com, Web: www.ottokemi.com

If swallowed

Rinse mouth. Give one or two glasses of water to drink. Refer for medical attention .

4.2Most important symptoms/effects, acute and delayed

Vapors irritate eyes and nose. Ingestion or skin contact causes headache, nausea, vomiting, dizziness. (USCG, 1999)

4.3 Indication of immediate medical attention and special treatment needed, if necessary

Immediate first aid: Ensure that adequate decontamination has been carried out. If patient is not breathing, start artificial respiration, preferably with a demand-valve resuscitator, bag-valve-mask device, or pocket mask, as trained. Perform CPR as necessary. Immediately flush contaminated eyes with gently flowing water. Do not induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration. Keep patient quiet and maintain normal body temperature. Obtain medical attention. /Ethylene glycol, glycols, and related compounds/

5. Fire-fighting measures

5.1Extinguishing media

Suitable extinguishing media

Carbon dioxide or dry chemical for small fires; alcohol-type foam for large fires.

5.2Specific hazards arising from the chemical

Excerpt from ERG Guide 128 [Flammable Liquids (Water-Immiscible)]: HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Those substances designated with a (P) may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water. Substance may be transported hot. For hybrid vehicles, ERG Guide 147 (lithium ion batteries) or ERG Guide 138 (sodium batteries) should also be consulted. If molten aluminum is involved, refer to ERG Guide 169. (ERG, 2016) 5.3Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

6.Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

6.2Environmental precautions

Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Remove all ignition sources. Collect leaking and spilled liquid in sealable containers as far as possible. Wash away remainder with plenty of water.

6.3Methods and materials for containment and cleaning up

Ventilate area of spill or leak. For small quantities, absorb on paper towels. Evaporate in safe place (such as fume hood). Allow sufficient time for evaporating vapors to completely clear hood ductwork. Burn paper in suitable location away from combustible materials. Large quantities can be collected and atomized in suitable combustion chamber. Waste disposal: By absorbing it in vermiculite, dry sand, earth or similar material and disposing in secured sanitary landfill; By atomizing in suitable combustion chamber.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Avoid exposure - obtain special instructions before use. Provide appropriate exhaust ventilation at places where dust is formed. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Separated from strong oxidants and food and feedstuffs. Cool. Keep in the dark. Separated from strong oxidants, food and feedstuffs. Cool. Keep in the dark

8.Exposure controls/personal protection

8.1Control parameters

Occupational Exposure limit values

Recommended Exposure Limit: 10 Hour Time-Weighted Average: 5 ppm (24 mg/cu m). Skin designation.

Biological limit values

no data available

8.2Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. 8.3Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection

Safety glasses with side-shields conforming to EN166. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Wear impervious clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique(without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves

101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208.

Tel: +91 9820041841

Email: info@ottokemi.com, Web: www.ottokemi.com

after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Respiratory protection

Wear dust mask when handling large quantities.

Thermal hazards no data available

9. Physical and chemical properties

Physical state clear liquid
Colour Colorless liquid
Odour Mild, ether-like odor
Melting point freezing point 240\u00b0C(lit.)
Boiling point or initial boiling point and boiling 169-172.5\u00b0C(lit.)

range

Flammability Class IIIA Combustible Liquid: Fl.P. at or above 60\u00b0C and below 93.33\u00b0C.Combustible.

Lower and upper explosion limit / flammability Lower flammable limit: 1.1% by volume @ 93\u00b0C; Upper flammable limit:12.7% by volume @

limit135\u00b0CFlash point67\u00b0CAuto-ignition temperature245\u00b0CDecomposition temperatureno data availablepHno data available

Kinematic viscosity 3.15 centistokes at 25\u00b0C

Solubility In water:miscible Partition coefficient n-octanol/water (log value) log Kow = 0.83

Vapour pressure <1 mm Hg (20 \u00b0C)
Density and/or relative density 0.902g/mLat 25\u00b0C(lit.)

Relative vapour density 4.1 (vs air)
Particle characteristics no data available

10.Stability and reactivity

10.1Reactivity no data available 10.2Chemical stability

Stable under recommended storage conditions.

10.3Possibility of hazardous reactions

Combustible liquid when exposed to hear or flame.ETHYLENE GLYCOL N-BUTYL ETHER may react with bases, aluminum and oxidizing materials. It is liable to form peroxides on exposure to air and light. It attacks some forms of plastics, rubber and coatings. .

10.4Conditions to avoid

no data available

10.5Incompatible materials

Forms explosive mixture with air. ... Violent reaction with strong caustics adn strong oxidizers. Attacks some coatings, plastics and rubber. Attacks metallic aluminum at high temperatures.

10.6Hazardous decomposition products

When heated to decomposition it emits acrid smoke and irritating fumes.

11.Toxicological information

Acute toxicity

Oral: LD50 Rat oral 470 mg/kg

Inhalation: LC50 Rat (male) inhalation 486 ppm/4 hr /from table/

Dermal: no data available Skin corrosion/irritation no data available

Serious eye damage/irritation

no data available

Respiratory or skin sensitization

Respiratory or ski no data available

Germ cell mutagenicity

no data available

Carcinogenicity

WEIGHT-OF-ÉVIDENCE CHARACTERIZATION: No reliable human epidemiological studies are available that address the potential carcinogenicity of EGBE. ... NTP /the National Toxicology Program/ reported no evidence of carcinogenic activity in male F344/N rats, and equivocal evidence of carcinogenic activity in female F344/N rats on the basis of increased combined incidences of benign and malignant pheochromocytoma (mainly benign) of the adrenal medulla. They also reported some evidence of carcinogenic activity in male B6C3F1 mice on the basis of increased incidences of hemangiosarcoma of the liver, and some evidence of carcinoma (mainly papilloma). ... because of the uncertain relevance of these tumor increases to humans, the fact that EGBE is

101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: +91 9820041841

Email: info@ottokemi.com, Web: www.ottokemi.com

generally negative in genotoxic tests and the lack of human data to support the findings in rodents, the human carcinogenic potential of EGBE, in accordance with the recently proposed Guidelines for Carcinogen Risk Assessment, cannot be determined at this time, but suggestive evidence exists from rodent studies. Under existing EPA guidelines, EGBE is judged to be a possible human carcinogen, Group C. There are currently no human epidemiological studies addressing the potential carcinogenicity of EGBE.

Reproductive toxicity no data available STOT-single exposure no data available STOT-repeated exposure no data available Aspiration hazard no data available

12. Ecological information

12.1Toxicity

Toxicity to fish: LC50; Species: Lepomis macrochirus (Bluegill); Conditions: static; Concentration: 1,490 mg/L for 96 hr

Toxicity to daphnia and other aquatic invertebrates: LC50; Species: Daphnia magna (Water flea); Conditions: static; Concentration:

1,720 mg/L for 24 hr

Toxicity to algae: no data available

Toxicity to microorganisms: no data available

12.2Persistence and degradability

AEROBIC: A number of aerobic biological screening studies, which utilized settled waste water, sewage, or activated sludge for inocula, indicate that ethylene glycol mono-n-butyl ether should biodegrade rapidly in the environment(1-4). Five and ten-day Theoretical BOD values were 73% (with acclimation)(1) and 74%(2). The maximum Theoretical BOD reported was 88% for 20 days(2).

12.3Bioaccumulative potential

An estimated BCF of 3 was calculated for ethylene glycol mono-n-butyl ether(SRC), using an estimated log Kow of 0.83(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is low (SRC).

12.4Mobility in soil

The Koc of ethylene glycol mono-n-butyl ether is estimated as 8(SRC), using a log Kow of 0.83(1) and a regression-derived equation(2). According to a classification scheme(3), this estimated Koc value suggests that ethylene glycol mono-n-butyl ether is expected to have high mobility in soil.

12.50ther adverse effects

no data available

13.Disposal considerations

13.1Disposal methods

Product

The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems. Contaminated packaging

Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.

IMDG: UN2810

IMDG: no

IATA: UN2810

IATA: no

14.Transport information

14.1UN Number

ADR/RID: UN2810 14.2UN Proper Shipping Name

ADR/RID: TOXIC LIQUID, ORGANIC, N.O.S.

IMDG: TOXIC LIQUID, ORGANIC, N.O.S. IATA: TOXIC LIQUID, ORGANIC, N.O.S.

14.3Transport hazard class(es)

ADR/RID: 6.1 IMDG: 6.1 IATA: 6.1

14.4Packing group, if applicable
ADR/RID: II IMDG: II IATA: II
14.5Environmental hazards

ADR/RID: no 14.6Special precautions for user

no data available

14.7Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

no data available

15.Regulatory information

101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: +91 9820041841

Email: info@ottokemi.com, Web: www.ottokemi.com

15.1Safety, health and environmental regulations specific for the product in question

Chemical name	Common names and synonyms	CA	S number	EC number
2-butoxyethanol	2-butoxyethanol	11	1-76-2	none
European Inventory of Existing Commercial Chemical Substances (EINECS)			Listed.	
EC Inventory			Listed.	
United States Toxic Substances Control Act (TSCA) Inventory			Listed.	
China Catalog of Hazardous chemicals 2015			Listed.	
New Zealand Inventory of Chemicals (NZIoC)			Listed.	
Philippines Inventory of Chemicals and Chemical Substances (PICCS)			Listed.	
Vietnam National Chemical Inventory				Listed.
Chinese Chemical Inventory of Existing Chemical Substances (China IECSC)				Listed.

Section 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.