

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1 Product identifiers

Product Name: Lithium bis(trifluoromethanesulfonyl)imide, anhydrous, 99.99%

Product Code: L 4710 CAS-No.: 90076-65-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use: Industrial. For professional use only.

1.3. Details of the supplier of the safety data sheet

Company identification OTTO CHEMIE PVT LTD

101, Aarkay Ruby Industrial Estate(1B), Opp Shree Narayan Industrial Estate,

Chinchpada, Vasai East, Waliv, Maharashtra 401208.

Email info@ottokemi.com

1.4. Emergency telephone number

Phone no.: + 91 22 2207 0099 (9:00am - 6:00 pm)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute toxicity, Oral (Category 3), H301 Acute toxicity, Dermal (Category 3), H311

Skin corrosion (Sub-category 1B), H314

Serious eye damage (Category 1), H318

Specific target organ toxicity - repeated exposure, Oral (Category 2), Nervous system,

Danger

Do not breathe dust.

protection.

Avoid release to the environment.

clothing. Rinse skin with water.

Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Signal Word

Hazard statement(s)

H301 + H311

H314

H373

Pictogram

H412

Precautionary statement(s)

P260

P273

P280

P303 + P361 + P353

P304 + P340 + P310

P305 + P351 + P338

Supplemental Hazard

Reduced Labeling Pictogram Signal Word

none Statements

(<= 125 ml)

rinsing.

Danger

DISCI AIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Toxic if swallowed or in contact with skin. Causes severe skin burns and eye damage.

prolonged or repeated exposure if swallowed.

Harmful to aquatic life with long lasting effects.

May cause damage to organs (Nervous system) through

Wear protective gloves/ protective clothing/ eye protection/ face

IF INHALED: Remove person to fresh air and keep comfortable

IF ON SKIN (or hair): Take off immediately all contaminated

for breathing. Immediately call a POISON CENTER/ doctor.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

otto chemie pvt ltd

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Hazard statement(s)

H314 Causes severe skin burns and eye damage. H412 Harmful to aquatic life with long lasting effects. H301 + H311 Toxic if swallowed or in contact with skin.

Precautionary statement(s)

P260 Do not breathe dust.

Wear protective gloves/ protective clothing/ eye protection/ face P280

protection.

IF ON SKIN (or hair): Take off immediately all contaminated P303 + P361 + P353

clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Immediately call a POISON CENTER/ doctor. IF IN EYES: Rinse cautiously with water for several minutes.

P305 + P351 + P338 Remove contact lenses, if present and easy to do. Continue

rinsing. none

Supplemental Hazard

Statements

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms: Bis(trifluoromethylsulfonyl)aminelithium salt

Lithium bistrifluoromethanesulfonimidate

Formula: C2F6LiNO4S2 Molecular weight: 287,09 g/mol CAS-No.: 90076-65-6 EC-No.: 415-300-0

Component	Classification	Concentration
lithium bis(trifluoromethylsulfonyl)imide		
CAS-No. 90076-65-6	Acute Tox. 3; Skin Corr.	<= 100 %
EC-No.415-300-0	1B; Eye Dam. 1; STOT RE	
	2; Aquatic Chronic 3;	
	H301, H311, H <mark>31</mark> 4, H318,	
	H373, H412	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Hydrofluoric (HF) acid burns require immediate and specialized first aid and medical treatment. Symptoms may be delayed up to 24 hours depending on the concentration of HF. After decontamination with water, further damage can occur due to penetration/absorption of the fluoride ion. Treatment should be directed toward binding the fluoride ion as well as the effects of exposure. Skin exposures can be treated with a 2.5% calcium gluconate gel repeated until burning ceases. More serious skin exposures may require subcutaneous calcium gluconate except for digital areas unless the physician is experienced in this technique, due to the potential for tissue injury from increased pressure. Absorption can readily occur through the subungual areas and should be considered when undergoing decontamination. Prevention of absorption of the fluoride ion in cases of ingestion can be obtained by giving milk, chewable calcium carbonate tablets or Milk of Magnesia to conscious victims. Conditions such as hypocalcemia, hypomagnesemia and cardiac arrhythmias should be monitored for, since they can occur after exposure. First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

First treatment with calcium gluconate paste. In case of skin contact: Take off immediately

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

OTTO CHEMIE PVT LTD

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible. Do not attempt to neutralise.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Nitrogen oxides (NOx)

Sulfur oxides

Hydrogen fluoride

Lithium oxides

Not combustible.

Ambient fire may liberate hazardous vapours.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Avoid generation and inhalation of dusts in all circumstances. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area.

Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Handle and store under inert gas. Moisture sensitive.

Storage class

Storage class (TRGS 510): 6.1B: Non-combustible, acute toxic Cat. 1 and 2 / very toxic

hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested: KCL 741 Dermatril® L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de). Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested:KCL 741 Dermatril® L

Body Protection protective clothing Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to

the used respiratory protection system. Recommended Filter type: Filter type P3

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure Do not let product enter drains.

OTTO CHEMIE PVT LTD

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties a) Physical state powder b) Color white

c) Odor No data available

d) Melting Melting point/range: 234 - 238 °C - lit.

point/freezing point e) Initial boiling point and boiling range

f) Flammability (solid, The product is not flammable. - Regulation (EC) No. 440/2008,

No data available

gas) Annex, A.10 g) Úpper/lower No data available

flammability or explosive limits h) Flash point

Not applicable i) Autoignition > 420 °C temperature - Regulation (EC) No. 440/2008, Annex, A.1 j) Decomposition No data available

temperature k) pH 7,0 - 9,5 at 10 g/l

I) Viscosity Viscosity, kinematic: No data available Viscosity, dynamic: No data available m) Water solubility ca.1.000 g/l - OECD Test Guideline 105

n) Partition coefficient: log Pow: -1,19 - OECD Test Guideline 107 - Bioaccumulation is n-octanol/water not expected.

< 0,000001 hPa at 25 °C - Regulation (EC) No. 440/2008, Annex, A.4 o) Vapor pressure ca.2,15 g/cm3 at 20 °C - OECD Test Guideline 109 p) Density

Relative density No data available q) Relative vapour No data available density

r) Particle No data available characteristics

s) Explosive properties No data available t) Oxidizing properties 9.2 Other safety information

SECTION 10: Stability and reactivity

10.1 Reactivity No data available

No data available

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

Violent reactions possible with:

Strong oxidizing agents

10.4 Conditions to avoid

no information available

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg: Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity to Animals: Not available.

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.

otto chemie pvt ltd

An ISO 9001: 2015 & GMP Certified Company

101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel: + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

Special Remarks on Chronic Effects on Humans: Not available. Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - 88,4

mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia

and other aquatic

invertebrates

static test EC50 - Daphnia magna (Water flea) - 14 mg/l - 48 h

(OECD Test Guideline 202)

Toxicity to algae static test ErC50 - Desmodesmus subspicatus (green algae) - 178

mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - activated sludge - > 1.000 mg/l - 3 h

(OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 9 % - Not readily biodegradable.

(OECD Test Guideline 302B)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 8 Weeks

at 25 °C(lithium bis(trifluoromethylsulfonyl)imide)

Bioconcentration factor (BCF): < 4

(OECD Test Guideline 305)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent.

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Assessment: The substance/mixture does not contain components

considered to have endocrine disrupting properties

according to REACH Article 57(f) or Commission

Delegated regulation (EU) 2017/2100 or Commission

Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 2923 IMDG: 2923 IATA: 2923

14.2 UN proper shipping name

CORROSIVE SOLID, TOXIC, N.O.S. (lithium bis(trifluoromethylsulfonyl)imide) ADR/RID: IMDG: CORROSIVE SOLID, TOXIC, N.O.S. (lithium bis(trifluoromethylsulfonyl)imide)

IATA: Corrosive solid, toxic, n.o.s. (lithium bis(trifluoromethylsulfonyl)imide)

14.3 Transport hazard class(es)

ADR/RID: 8 (6.1) IMDG: 8 (6.1) IATA: 8 (6.1)

14.4 Packaging group

ADR/RID: II IMDG: II IATA: II

14.5 Environmental hazards

DISCLAIMER

Otto Chemie Pvt Ltd - products are only for laboratory use only. Not for drug, medicinal, household or any other use. No liability accepted for mishandling in use - please test before use

Otto Chemie Pvt Ltd - shall not be responsible for any damage resulting from handling or from contact with the above product.



An ISO 9001 : 2015 & GMP Certified Company 101, Aarkay Ruby Industrial Estate (1B), Opp Shree Narayan Industrial Estate, Chinchpada, Vasai East, Waliv, Maharashtra 401208. Tel : + 91 98200 41841

Email: info@ottokemi.com Web: www.ottokemi.com

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user Tunnel restriction code : (E)

Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No.

1907/2006.

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

Section 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

