

OTTO CHEMIE PVT LTD

201, 51-53 Maroo Bhavan, Kalbadevi, Mumbai – 400002, India. Tel : + 91 22 2207 0099 / 6638 2599

Email : info@ottokemi.com, Web : www.ottokemi.com

ISO 9001: 2015

MATERIAL SAFETY DATA SHEET

SECTION 1 Product identifiers

Product name : Petroleum ether 60-80 °C, GR

Product Code: P 1454

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225

Acute toxicity, Oral (Category 4), H302

Skin irritation (Category 2), H315

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

Aspiration hazard (Category 1), H304

Long-term (chronic) aquatic hazard (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapor.

H302

Harmful if swallowed.

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

H336

May cause drowsiness or dizziness.

H411

Toxic to aquatic life with long lasting effects.

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273

Avoid release to the environment.

P301 + P310 + P331

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

P301 + P312 + P330

IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P302 + P352

IF ON SKIN: Wash with plenty of water.

Supplemental Hazard Statements

none

Reduced Labeling

(<= 125 ml)

Pictogram

Signal word

Danger

Hazard statement(s)

H304

May be fatal if swallowed and enters airways.

Precautionary statement(s)

P301 + P310 + P331

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do

NOT induce vomiting.

Supplemental Hazard

none

Statements

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Synonyms : Petroleum benzin

Component	Classification	Concentration
Hydrocarbons, C6, isoalkanes, <5% n-hexane		
EC-No. 931-254-9	Flam. Liq. 2; Acute Tox. 4; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1; Aquatic Chronic 2; H225, H302, H315, H336, H304, H411	>= 50 - <=100 %
pentane		
CAS-No. 109-66-0 EC-No. 203-692-4	Flam. Liq. 2; STOT SE 3; Asp. Tox. 1; Aquatic Chronic 2; H225, H336, H304, H411 Concentration limits: 20 %: STOT SE 3, H336;	>= 25 - <=50 %

*A registration number is not available for this substance as the substance or its use are exempted from registration according to Article 2 REACH Regulation (EC) No 1907/2006, the annual tonnage does not require a registration or the registration is envisaged for a later registration deadline.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Consult a physician. Show this material safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration.

Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry powder Dry sand

Unsuitable extinguishing media

Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Flash back possible over considerable distance., Container explosion may occur under fire conditions.

Combustible.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,4 mm

Break through time: 480 min

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,2 mm

Break through time: 30 min

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a fullface respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form:	liquid, clear Color: colorless
b) Odor	No data available
c) Odor Threshold	No data available
d) pH	No data available
e) Melting point/freezing point	No data available
f) Initial boiling point and boiling range	40 - 60 °C
g) Flash point	< -30 °C
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 7 %(V) Lower explosion limit: 1 %(V)
k) Vapor pressure	No data available
l) Vapor density	No data available
m) Relative density	No data available
n) Water solubility	immiscible
o) Partition coefficient: n-octanol/water	No data available
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact. Toxicity to Animals:

Oral LD50 Rat: 1500 mg/kg; Dermal LD50 Rabbit: 2000mg/kg

Inhalation LC50 Rat: > 50mg/L.

Chronic Effects on Humans: CARCINOGENIC EFFECTS: Classified None. by NTP, None. by OSHA, None. by NIOSH.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of inhalation (lung irritant).

Special Remarks on Toxicity

to Animals: Not available.

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Toxic to aquatic life with long lasting effects.

Components

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Toxicity to fish LC50 - Fish - 2 mg/l - 96 h

Remarks: No data available

pentane

Toxicity to fish static test LC50 - Oncorhynchus mykiss (rainbow trout) - 4,26

mg/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia

and other aquatic

invertebrates

static test EC50 - Daphnia magna (Water flea) - 2,7 mg/l - 48

h

Remarks: (ECHA)

Toxicity to algae static test ErC50 - Selenastrum capricornutum (green algae) -

10,7 mg/l - 72 h

(OECD Test Guideline 201)

static test NOEC - Selenastrum capricornutum (green algae) -

7,51 mg/l - 72 h

(OECD Test Guideline 201)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1268

IMDG: 1268

IATA: 1268

14.2 UN proper shipping name

ADR/RID: PETROLEUM DISTILLATES, N.O.S.

IMDG: PETROLEUM DISTILLATES, N.O.S. (Hydrocarbon mixture C5-C8 Aliphates)

IATA: Petroleum distillates, n.o.s.

14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

14.5 Environmental hazards

ADR/RID: yes

IMDG Marine pollutant: yes

IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

National legislation

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

: ENVIRONMENTAL HAZARDS

: FLAMMABLE LIQUIDS

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

Section 16: Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

